


D Range | undercounter



D502

- **2 year warranty**
- **NEW** four button bright LED display with soft touch controls, twin traffic lights giving instant status updates & operational self-diagnostics
- **NEW** alarms menu with hi-level information retrieval
- **NEW** improved wash action from quick release parallel wash & rinse arm design
- **NEW** improved triple wash tank filtration system
- Drain pump fitted as standard
- Three standard cycle time options with a range of special cycles
- Cycle times can be tailored to site requirements
- Reduced water consumption
- Comprehensive automatic self-cleaning at end of service
- Selectable energy saving mode
- Selectable thermostop ensures optimum rinse temperatures
- Fully double skinned minimising both acoustic output and reduced heat-loss
- Patented dual flow wash pump with **soft start** – reducing power consumption whilst retaining wash efficiency
- Full door seal and door ajar facility
- Moulded wash tank for easy cleaning
- Moulded rack guide
- Surface scrap tray filters supplied as standard
- Accurate detergent & rinse aid peristaltic dosing pumps as standard
- Supplied with two open cup/glass racks & cutlery insert



NEW four button bright LED display with soft touch controls & twin traffic lights giving instant status updates

Technical

- Standard voltage 230V – single phase (can be supplied for 3 phase – please specify at time of order)
- Suitable for hot (max 50°C) or cold water supply, typically at 2 to 4 bar dynamic supply pressure, refer to specification sheets for individual requirements
- Wash temperature 60°C (adjustable)
- Rinse temperature 65°C (adjustable)
- Cycle times between 70 & 240 secs, dependent on model

Requires a waste up stand for correct operation. Restrictive waste connections should be avoided for all installations.

All 500 basket machines supplied 13 amp will come with moulded plug and cable.

Machine configured for 13 amp supply or fitted to cold water supply will not be capable of running repeated short cycles. The cycle time will automatically be extended to allow for recovery of correct operating temperatures.

Model	Rack size mm	Useable Height mm	Dimensions mm W x D x H	Cycle Options	Power kW	Amps Required
D502	500	260	600 x 600 x 710 [#]	3 Cycles	2.6/4.5/6.5	13/20/30 ^{##}

[#] Height excludes adjustable feet which will add 10 to 20mm.

^{##} Machines will be supplied for 30 amp supply as standard. If supplied 13 amp machine will come fitted with moulded plug and cable.

20 amp machines will be supplied with original cable and without plug. Standard 13 amp UK 3 pin plugs will be **unsuitable** for cable supplied.