



CMPXS - RATIONAL CombiMaster Plus Electric Counter-top Combi Oven - Model XS - W 655 mm - 5.7 kW - 3 Phase

This clever, compact RATIONAL CombiMaster® Plus packs just as much punch as the larger models — just condensed into a smaller yet still spacious machine.

- ✓ The perfect solution where space is at a premium, a compact 6 x 2/3 GN unit with exactly the same performance and functionality as larger models
- ✓ Compact in design, yet spacious enough to fit six 2/3GN pans, this oven squeezes the same impressive features and performance as the larger GN 1/1 and GN2/1 versions into a smaller, more convenient machine. Whether it's being used as your main front of house unit or as vital additional capacity during busy hours, you can rely on the CombiMaster® to bake, roast, steam or regenerate quickly and easily.
- ✓ Perfect for anyone who is looking for a classic combi-steamer and wishes to operate it manually, saves time and money on energy and raw materials
- ✓ Four cooking modes: hot air cooking, steam cooking, combination cooking and Finishing®
- ✓ Simple to use manual controls and highly efficient LED lighting, which makes the CombiMaster® ideal for working areas with limited space, such as service stations, cafés, takeaways and more.
- ✓ Optimum cabinet climate with ClimaPlus® gives you control of the cabinet humidity for perfect results
- ✓ Programming function - Individual programming of 100 cooking programs each with up to 6 steps
- ✓ Precise core temperature probe

Specifications

Summary		Power and Performance	
Brand	Lincat	Total Power kW	5.7
Range	RATIONAL	Temperature Range °C	30-300
Series	CombiMaster Plus	IP Rating	IPX5
Power Type	Electric	Temperature Control	Electronic
Unit Type	Counter-top	Oven Rating kW	Steam connection = 5.4; Hot air connection = 5.4
Available in UK Only	Yes		
UK Warranty	RATIONAL 2 Years Parts and Labour Warranty		

Key Specifications		Capacity	
WRAS Approved	Yes	Gastronorm Capacity	6 x GN2/3
Type of Lighting	LED	Portions per Day	20-80 meals per day
Number of Grids included	0		

Distributor:
KiD Catering Equipment, Oaktree Court Business Centre, Mill Lane, Ness, Cheshire, CH64 8TP
Tel: 0333 123 2450 sales@kidcateringequipment.com

Weights and Dimensions		Supply Connections	
Unit Height (External) mm	567	Requires Installation	Yes
Unit Width (External) mm	655	Requires Electrical Supply	Yes
Unit Depth (External) mm	555	UK 3 Pin Plug	No
Height (Internal) mm	509	Requires Hardwiring	Yes
Width (Internal) mm	608	Electrical Supply Rating Watts	5,700
Depth (Internal) mm	495	Three Phase Amps	L1=8.3; L2=8.3; L3=8.3
Net Weight Kg	62	Three Phase Voltage	400
		Water Connection Pressure Bar	6
		Drain Connection	DN 50 mm
		Water Connection	3/4"

Shipping	
Packed Weight Kg	68.2
Packed Height cm	80
Packed Width cm	80
Packed Depth cm	80

Distributor:
 KiD Catering Equipment
 Oaktree Court Business Centre
 Mill Lane, Ness,
 Cheshire
 CH64 8TP
 Tel: 0333 123 2450
sales@kidcateringequipment.com