


ACTIVA 7 TRAYS 20 kg

Standard features:

Plug-in with air condensation, R452A unit

Hinges on the right, non-reversible door

Drain on the bottom, standard drip tray included

Bivalent trays support GN 1/1 and EN 60x40

Blast Chilling

20 kg

 +90°C → +3°C
90 min

Deep Freezing

12 kg

 +90°C → -18°C
240 min

Capacity

7 GN 1/1
(7 EN60x40)
CONSUMPTION (prEN 17032)

Blast Chilling	Deep Freezing
+90°C / +3°C	+90°C / -18°C
0,12 kWh/kg	0,40 kWh/kg

REFRIGERANT GAS

Type	GWP	Charge
R452A	2141	0,9 kg

ROOM CONDITIONS

+32°C

60% UR

CERTIFICATION

TECHNICAL DATA

Code	MXT7.20
Version	Air
Dimensions (L x P x H)	798 x 815 x 995/1025 mm
Net Weight	120 kg
Insulation Thickness	70 mm
Standard Tension	230 V / 1 Ph / 50 Hz
Power Consumption	1,3 kW / 7,0 A
Refrigeration power (*Te= -10 °C)	1.750 W
Refrigeration power (*Te= -30 °C)	700 W
Noise	<70 dB
HP	1,0 HP

*Expansion temperature - Condensation temperature

SPECIFICATIONS IN COMPLIANCE WITH prEN 17032

Blast Chilling (+65°C / +10°C)		Deep Freezing (+65°C / -18°C)	
Maximum capacity	Time	Maximum capacity	Time
20 kg	120 min	12 kg	260 min

Distributor:

 KiD Catering Equipment, Oaktree Court Business Centre, Mill Lane, Ness, Cheshire, CH64 8TP
 Tel: 0333 123 2450

sales@kidcateringequipment.com

CONTROLLER

							
BLAST CHILLING	DEEP FREEZING	STANDARD CORE PROBE	AUTOMATIC CONSERVATION	RAW FISH SANITATION	HACCP ALARMS	HEATED CORE PROBE (OPTIONAL)	STERILIZER (OPTIONAL)

Available cycles:

- Temperature-blast chilling with core probe + conservation phase;
- Time-blast chilling time without core probe + conservation phase;
- Temperature-deep freezing with core probe + conservation phase;
- Time-deep freezing without core probe + conservation phase;
- SOFT and HARD cycles for both blast chilling +3°C or deep freezing -18°C;
- Pre-cooling cycle.

Special functions:

- Automatic control on core probe insertion;
- Core probe temperature visualization;
- Visualization of elapsed time from start, customizable by user;
- Raw fish sanitation cycle;
- Manual defrost.


CONSTRUCTIVE FEATURES

Stainless steel structure AISI 304 18/10, external Scotch-Brite, internal mirror finish; rounded inner and outer angles for a perfect and easy cleaning; space under the evaporator for a perfect cleaning; oversized condenser to ensure reliability; Italian high-performance refrigerating units; special fans suitable for low temperatures; evaporators with cataphoresis anticorrosion treatment; the technical room of evaporator and condenser can be easily inspected.

ACCESSORIES

	Kit 4 Castors ACC 140		Left Opening Door ACC 135
	Ozone sterilizer* ACC 110		Heated Core Probe* ACC 509
	Trays support EN 60x40 ACC 800/2		LED Light ACC 147


*We can choose one of the two options

Distributor:


KiD Catering Equipment, Oaktree Court Business Centre, Mill Lane, Ness, Cheshire, CH64 8TP
 Tel: 0333 123 2450
sales@kidcateringequipment.com

DIMENSIONS


Front View



Side View



Top View



CONNECTIONS

- A = Electrical connection
- B = Water connection (if required)
- C = Evaporator water drain pipe
- D = Refrigeration Connection (if required)