STERLING PRO

Green Single Door Cabinets

SPI600 & SNI600

2 YEARS WARRANTY

2-3 DAY DELIVERY

UK SERVICE SUPPORT

MADE IN THE EU

Specifications

Model	Type	Hinge	Capacity Gross	Capacity Nett	Temperature	Annual Energy Consumption	Dimensions (mm) Width	Dimensions (mm) Depth	Dimensions (mm) Height	Energy Rating	Refrigerant
SPI600R	Fridge	Right	600 ltrs	386 ltrs	-2°C to +8°C	548 kWh	693	726	2067	C	R290a
SPI600L	Fridge	Left	600 ltrs	386 ltrs	-2°C to +8°C	548 kWh	693	726	2067	C	R290a
SNI600R	Freezer	Right	600 ltrs	386 ltrs	-18°C to -22°C	2179 kWh	693	726	2067	D	R290a
SNI600L	Freezer	Left	600 ltrs	386 ltrs	-18°C to -22°C	2179 kWh	693	726	2067	D	R290a

Key Features

- Power supply: 13 amp plug
- Hinged doors with automatic return
- Stainless Steel interior and exterior
- Forced draft evaporator
- 18 grid level positions for increased loading capacity
- Lockable door with replacement gaskets
- Intelligent air-circulation system
- 50mm high-density injected insulation

Distributor:
KiD Catering Equipment, Oaktree Court Business Centre, Mill Lane, Ness, Cheshire, CH64 8TP
Tel: 0333 123 2450 sales@kidcateringequipment.com

Green Single Door Cabinets

SPI600 & SNI600

Efficiency

- "Ventilation Gill" on the front panel keeping the cooling unit system ventilated and running more efficiently.
- Forced draft evaporator with anti-corrosion cover.
- Intelligent Air Circulation system ensures perfect temperature consistency with its innovative airflow design.
- Door switch stops the fan when door is opened to avoid cold air exiting the interior, thus saving energy.
- 50 mm thickness, CFC-free, high-density (40 kg/m³) polyurethane insulation, injected under high pressure

Features

- Space saving design - only 726mm deep.
- Specially manufactured in high-quality Stainless Steel for intensive professional applications, featuring a very robust design and perfect finishing.
- Placing and adjusting the wire grids at the desired heigh is possible without using extra rails. Epoxy-coated wire grids, to improve protection, allow storage of different packaging types and have a maximum loading capacity of up to 40kg.
- Removable pull-out/ push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties.
- Stamped bottom panel with water drain especially designed to make cleaning operations quicker and easier, optimum for hygiene.
- Rounded edge interiors, easier cleaning operations to reduce potential dirt traps.
- 18 grid level positions for increased loading capacity, with a distance of 70mm between them.
- Automatic evaporation of defrost water. Hot gas from the compressor is used to automatically evaporate defrost water, instead of using a heating element, achieving even less energy consumption and reducing the defrosting time by half.
- Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and closes automatically at less than 90°. Door hinges are also reversible allowing the cabinet to be adapted on-site.
- Intuitive digital control allows temperature parameters to be adjusted easily and quickly.
- Luminous start-stop light button.

Contact

Distributor:
KiD Catering Equipment, Oaktree Court Business Centre, Mill Lane, Ness, Cheshire, CH64 8TP
Tel: 0333 123 2450 sales@kidcateringequipment.com